

HP LaserJet 3015 all-in-one



Close

specifications

Print	<ul style="list-style-type: none">• Print speed: Up to 15 ppm¹• First page out: 10 seconds• Print resolution: 1200 dpi effective output resolution (600 x 600 dpi with Resolution Enhancement technology (REt) and FastRes 1200)• Printer language: HP PCL 6, HP PCL 5e, PostScript® Level 2 emulation• Printer technology resolution: Resolution Enhancement technology (REt), FastRes 1200• Duty cycle, monthly: 7,000 pages
Scan	<ul style="list-style-type: none">• Scan resolution (color & black and white): 9600 x 9600 dpi enhanced, 600 x 600 dpi optical• Scan input: Device front control panel scan, e-mail, file buttons; HP LaserJet Scan software; TWAIN-compliant or WIA-compliant software• Bit depth: 24-bit• Scan size (from ADF): 2.9 x 4.1 in to 8.5 x 14 in• Scan technology: Contact Image Sensor (CIS)
Copy	<ul style="list-style-type: none">• Copy speed: Up to 15 cpm• First copy out: 15 seconds• Copy resolution: 600 x 600 dpi• Reduction/enlargement: 25 to 400%• Maximum copies: 99 copies• Copier settings: Contrast (lighter/darker), resolution (copy quality), reduce/enlarge, copy collation, number of copies, paper size
Fax	<ul style="list-style-type: none">• Fax speed: 3 sec per page (Slerexe page, standard resolution)• Fax resolution: Best: 300 x 300 dpi (no halftone), fine: 203 x 196 dpi, photo: 300 x 300 dpi (halftone enabled)• Fax memory: Up to 110 sheets• Fax speed dial (max. number): 120 numbers (110 group dials)• Fax settings: Faxing from ADF, auto redial, billing codes, fax forwarding, fax auto-reduction, block fax barrier, fax delayed sending, polling-receive, distinctive ring detection• Fax modem: V.34 fax modem (up to 33.6 Kbps) + 2 RJ-11 ports
Paper handling	<ul style="list-style-type: none">• Automatic document feeder: Standard• Automatic two-sided printing/copying: Manual• Media handling: Media input tray: 150 sheets; priority input tray: 10 sheets; automatic document feeder (ADF): 30 sheets• Output: 125 sheets• Media types: Paper (plain, preprinted, prepunched, bond, color, glossy, letterhead, light, heavy, recycled, rough), envelopes, transparencies, labels, cardstock• Media sizes and weights: Media input tray and priority input slot: letter, legal, US envelope No. 5 (1/2 Baronial) through No. 11, US A2, US A6, index cards, US postcard; 3 x 5 to 8.5 x 14 in (16 to 43 lb); automatic document feeder (ADF): letter, legal; 5 x 5 to 8.5 x 14 in (16 to 24 lb); output bin: 16 to 28 lb
Memory	32 MB RAM, 2 MB fax memory
Processor	240 MHz
Interface connectivity	<ul style="list-style-type: none">• Parallel: IEEE 1284-B level 2 device with an IEEE 1284-B receptacle with the host computer set to ECP• USB: compatible with 2.0 specifications
Dimensions	16.75 x 18.5 x 17.5 in
Weight	20.8 lb

Minimum system requirements	Windows® 98 Second Edition, 2000, Me, XP, Win NT 4.0 print driver only; Mac® OS 9.1, 9.2.x, Mac OS X v10.2.x available on Web; DOS, Linux, UNIX, OS/2 print functionality only available on Web
Environmental ranges	<ul style="list-style-type: none"> • Recommended operating temperature: 59 to 90.5° F (15 to 32.5° C) • Recommended operating humidity: 10 to 80% RH • Storage humidity: 0 to 95% RH
Acoustics	<ul style="list-style-type: none"> • Sound pressure: 49 dB(A) • Sound power: 6.2 B(A) LwAd (printing at 15 ppm)
Power requirements	Input voltage: Input voltage 110 to 127 VAC (±10%), 50/60Hz (±2Hz), 4.5 amp
Power consumption	300 watts (average during printing), 7 watts (average standby), 7 watts (average PowerSave mode), 0-watt (average off)
Power certification	<ul style="list-style-type: none"> • Safety certification: IEC 60950: 1999/EN60950: 2000; IEC 60825–1: 1993 + A1: 1996 + A2: 2001/EN 60825–1: 1994 + A11: 1996 + A2: 2001 (Class 1 Laser/LED Product); GB4943-1995 • Electromagnetic compatibility: CISPR 22: 1998/EN 55022:1998 - Class B; EN 61000–3-2: 1995/A14:2000; EN 61000–3-3: 1995; EN 55024: 1998; FCC Title 47 CFR, Part 15 Class B 2/ICES-003, Issue 3; GB9254-1998; Telecom: TBR-21: 1998; EG 201 121: 1998, FCC Part 68, Industry Canada CS03 • ENERGY STAR® compliant

Notes:

* Based on 5% average page coverage.

Brands and product names herein are trademarks or registered trademarks of their respective holders.
© 2003 Hewlett-Packard Company

Close